

magazine Buffer stacker

Equipment Data Sheet

Model:	EMB-370
Frame Style:	Extruded aluminum frame with painted vanity panels
Description:	Designed to minimize stand by time between previous and next machine in the line. Magazine rack loading capacity: Max. 5 magazine racks (Top : 2 racks, Lower : 3racks) Able to perform as loader / unloader / rack buffer stacker

Standard Features:

- PCB size: 50 x 50 up to 530 x 460
- Various functions : Loader / Unloader / Rack buffer stacker
- Store and load the worked PCB to next process
- Loaded by First-In First-Out / Last-In First-Out / Pass : at the rack buffer function
- Accurate positioning : Inner Data comparison
- Programmable Logic Controller
- 3 color light tower lamp with audible alarm
- Load up to 5 magazine racks : Top 2 magazine racks, Lower 3 magazine racks
- Left to right travel, front fixed rail
- Conforms to SMEMA Spec. 1.2

Options:

- Utilized the failed board staker
- ESD grounding receptacles
- Touch screen of operating panel
- Auto or Semi-auto width adjust
- Safety cover

Facilities Requirements:

Electrical:	AC220V 50-60Hz 1 Phase
Conveyor height	900mm+/-30mm / 950mm+/-30mm
Air:	5 kgf/cm2
Power consumption	Max. 200W, 1A



Manufactured Exclusively by EUNIL