

# *manual insertion conveyor*

## Equipment Data Sheet

<b>Model:</b>	<b>EMC / EFC / EAC</b>
<b>Frame Style:</b>	Extruded aluminum frame with painted vanity panels
<b>Description:</b>	Intelligent variable belt type of the conveyor that can be used as a linear work station for manual inserting production line.

### Standard Features:

- PCB Size: 50 x 50 – 530 x 460
- Programmable Logic Controller
- Speed control : 0 - 182mm/sec (50Hz) / 194mm/sec (60Hz)
- Hand crank width adjusting
- Pneumatic Stopper
- Constant conveyor running
- Economic space
- Left to right travel, front rail fixed
- Conforms to SMEMA Spec. 1.2

### Options:

- ESD grounding receptacles
- Auto or Semi-auto width adjust
- Conveyor tilting angle (EAC) : 15° / 30°
- Variable buffer stations
- Variable belt type : Edge belt / Chain / Flat belt
- Length : 1, 2, or 3M

### Facilities Requirements:

<b>Electrical:</b>	AC220V 50-60Hz 1 Phase
<b>Conveyor height</b>	900mm+/-30mm / 950mm+/-30mm
<b>Air:</b>	5 kgf/cm <sup>2</sup>
<b>Power consumption</b>	Max. 200W, 1A



Manufactured Exclusively by EUNIL